

## Configuration summary

| Mat. no. | Description<br>Order code              | Quantity | Unit |
|----------|----------------------------------------|----------|------|
| 52023172 | Soliphant M FTM50<br>FTM50-6GG2A4A52AA | 1        | ST   |

|     |                               |    |                                                         |
|-----|-------------------------------|----|---------------------------------------------------------|
| 010 | Approval:                     | 6  | ATEX II 1/2 D Ex t IIIC T90oC ATEX II 1/2 G Ex d IIC T6 |
| 020 | Process Connection:           | GG | Thread EN10226 R1-1/2                                   |
| 030 | Material; Surface Refinement: | 2  | 316L; Ra<=3.2um/126uin, w/o                             |
| 040 | Fork; Bulk Density:           | A  | 155mm/6inch; min 10g/l standard fork                    |
| 050 | Electronics; Output:          | 4  | FEM54; relay DPDT, 19-253VAC/55VDC                      |
| 060 | Type of Probe:                | A  | Compact                                                 |
| 070 | Housing:                      | 5  | F13 Alu IP66/68 NEMA Type 4X Encl.                      |
| 080 | Cable Entry:                  | 2  | Gland M20 (Ex d > thread M20)                           |
| 090 | Additional Option 1:          | A  | Not selected                                            |
| 100 | Additional Option 2:          | A  | Not selected                                            |