

## Configuration summary

| Mat. no. | Description<br>Order code                  | Quantity | Unit |
|----------|--------------------------------------------|----------|------|
| 60019602 | RTD Thermometer TR10<br>TR10-AAF3BHSF9C000 | 1        | ST   |

|     |                                          |    |                                          |
|-----|------------------------------------------|----|------------------------------------------|
| 010 | Approval:                                | A  | Non-hazardous area                       |
| 020 | Head; Cable Entry:                       | A  | **TA20A Alu, IP66/IP67; M20              |
| 030 | Pipe Diameter; Material:                 | F  | 12 mm; 316Ti, DIN43772-2G/3G             |
| 040 | Neck Length E:                           | 3  | 145 mm, DIN43772-2G                      |
| 050 | Process Connection:                      | BH | Thread G1/2 A DIN43772; 316Ti            |
| 060 | Tip Shape:                               | S  | Straight                                 |
| 070 | Immersion Length L:                      | F  | 250 mm                                   |
| 080 | Head Transmitter; Range:                 | 9  | Special version, TSP-no. to be spec.     |
| 090 | RTD; Wire; Meas. Range; Class; Validity: | C  | 1xPt100 WW; 4; -200/600oC; A; -200/600oC |
| 100 | Material Certificate:                    | 0  | Not needed                               |
| 110 | Test Report:                             | 0  | Not needed                               |
| 120 | Test/Calibration:                        | 0  | Not needed                               |