

# Configuration summary

| Mat. no. | Description<br>Order code                     | Quantity | Unit |
|----------|-----------------------------------------------|----------|------|
| 71086209 | Cerabar M PMP51<br>PMP51-AA32QA1SGBGRJA1+AAF1 | 1        | ST   |

|     |                                 |     |                                                                                            |
|-----|---------------------------------|-----|--------------------------------------------------------------------------------------------|
| 010 | Approval:                       | AA  | Non-hazardous area                                                                         |
| 020 | Output:                         | 3   | PROFIBUS PA                                                                                |
| 030 | Display, Operation:             | 2   | W/o LCD, push button on electronics                                                        |
| 040 | Housing:                        | Q   | F15 stainless steel hygiene                                                                |
| 050 | Electrical Connection:          | A   | Gland M20, IP66/68 NEMA4X/6P                                                               |
| 070 | Sensor Range:                   | 1S  | 40bar/4MPa/600psi gauge,<br>400mH2O/1334ftH2O/16000inH2O<br>overload: 160bar/16MPa/2400psi |
| 080 | Reference Accuracy:             | G   | Standard                                                                                   |
| 090 | Calibration; Unit:              | B   | Sensor range; mbar/bar                                                                     |
| 110 | Process Connection:             | GRJ | Thread ISO228 G1/2, shape E, 316L,<br>flush mount                                          |
| 170 | Membrane Material:              | A   | 316L                                                                                       |
| 180 | Fill Fluid:                     | 1   | Silicone oil                                                                               |
| 500 | >Additional Operation Language: | AA  | English                                                                                    |
| 550 | >Calibration:                   | F1  | Works calib. certificate 5-point                                                           |