

# Configuration summary

| Mat. no. | Description<br>Order code                | Quantity | Unit |
|----------|------------------------------------------|----------|------|
| 71008645 | Deltapilot S FMB70<br>FMB70-ACR1CA200CAA | 1        | ST   |

|     |                                      |    |                                                                                  |
|-----|--------------------------------------|----|----------------------------------------------------------------------------------|
| 010 | Approval:                            | A  | Non-hazardous area                                                               |
| 020 | Output; Operating:                   | C  | 4-20mA HART; inside                                                              |
| 030 | Housing; Cover Sealing; Cable Entry: | R  | T17 316L hygiene IP66/68<br>NEMA6P;EPDM;M20 gland, T17 =<br>side cover           |
| 040 | Sensor Range; Sensor Overload Limit: | 1C | 100mbar/10kPa/1.5psi/1mH2O/40inH2<br>O<br>4bar/400kPa/60psi/40mH2O/1600inH2<br>O |
| 050 | Calibration; Unit:                   | A  | Sensor range; %                                                                  |
| 060 | Membrane Material; Seal:             | 2  | AlloyC276; welded                                                                |
| 070 | Process Connection:                  | 00 | Universal adapter 44mm 316L, 3A,<br>EHEDG, incl. silicone shape seal             |
| 090 | Fill Fluid:                          | C  | Synthetic oil (FDA)                                                              |
| 100 | Additional Option 1:                 | A  | Not selected                                                                     |
| 110 | Additional Option 2:                 | A  | Not selected                                                                     |