


AC1220

PSU-1AC/ASI-1.0A

Bus system AS-Interface

no longer available - archive entry



Product characteristics

Power supply

AS-i power supply 100...240 V AC

Integrated data decoupling

30 Watt

Application

Application AS-i system voltage for masters, sensors, actuators and modules

Electrical data

Input voltage range	[V]	100...240 AC ($\pm 10\%$)
Nominal frequency	[Hz]	47...63
Output voltage (AS-i)	[V]	29.5...31.6 DC
Output current (AS-i)	[A]	0.95
Residual ripple	[mV]	< 50
Efficiency	[%]	86 (230 V AC / 24 V DC)
Short-circuit proof		yes
Overload protection		yes
Overvoltage protection	[V]	< 34
Fuse	[A]	10; external, characteristics B
Power-on delay time	[ms]	≤ 255
Derating	[W/K]	2% / K ($> +60^{\circ}\text{C}$)
Mains buffering time	[ms]	120 (230 V AC)
Protection class		II

Outputs

Output 30 Watt

Environment

Ambient temperature	[$^{\circ}\text{C}$]	0...70
Protection		IP 20

Tests / approvals

EMC	EN 61000-6-2 EN 61000-6-3
-----	------------------------------

AS-i classification

AS-i certificate 91101

Mechanical data

AC1220

PSU-1AC/ASI-1.0A


Bus system AS-Interface

Housing materials	PC; ABS
Installation	rail TH35 (to EN 60715)
Weight [kg]	0.336

Displays / operating elements	
Function display	LED green (indication AS-i voltage)

Electrical connection	
Connection	cage clamps; Core cross-section ≤ 1.5 mm² (AWG16)

Wiring



- 1: primary
- 2: secondary

Remarks	
Remarks	Observe the free space for convection (30 mm)
Pack quantity [piece]	1

no longer available - archive entry