

# KB5096




## Capacitive sensor

KB-3020-APKG/NI/US-100-DPO

Article no longer available - archive entry

Alternative articles: KI5304 + E10077

When selecting an alternative article and accessories please note that technical data may differ!



### Product characteristics

Electrical design		PNP
Output function		normally closed
Sensing range	[mm]	20
Housing		tubular
Dimensions	[mm]	Ø 34 / L = 93

### Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	13; (24 V)
Protection class		II
Reverse polarity protection		yes

### Outputs

Electrical design		PNP
Output function		normally closed
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	40
Short-circuit proof		yes
Overload protection		yes

# KB5096



## Capacitive sensor

KB-3020-APKG/NI/US-100-DPO

Monitoring range		
Sensing range	[mm]	20
Sensing range adjustable		yes
Factory setting sensing range	[mm]	20
Real sensing range Sr	[mm]	20 ± 10 %
Operating distance	[mm]	0...16.2

Accuracy / deviations		
Correction factor		glass: 0.4 / water: 1 / ceramics: 0.2 / PVC: 0.2
Hysteresis	[% of Sr]	3...15
Switch-point drift	[% of Sr]	-15...15

Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 65
Increased immunity		yes; (Increased immunity to conducted radio frequency interference)

Tests / approvals		
EMC		EN 60947-5-2
MTTF	[years]	778

Mechanical data		
Weight	[g]	167.8
Housing		tubular
Mounting		non-flush mountable
Dimensions	[mm]	Ø 34 / L = 93
Material		PBT

Displays / operating elements		
Display	Switching status	1 x LED, yellow

Accessories		
Items supplied		Mounting clamp: 1 screwdriver: 1

Remarks		
Pack quantity		1 pcs.

### Electrical connection - plug

Connector: 1 x M12



# KB5096



## Capacitive sensor

KB-3020-APKG/NI/US-100-DPO

### Connection

