

# Product datasheet

Specifications



## RS485 interface 2 wires ACE949-2 for Sepam 20, 40, 60, 80



59642

### Main

range of product	Sepam series 60 Sepam series 80 Sepam series 40 Sepam series 20 Sepam series 48 Sepam series 80 NPP
------------------	--

Device short name	ACE949-2
-------------------	----------

### Complementary

Communication port protocol	Modbus RTU network: E-LAN interface: RS485 - 2-wire Modbus RTU network: S-LAN interface: RS485 - 2-wire
-----------------------------	--

Local signalling	LED for link activity (front face)
------------------	------------------------------------

[Us] rated supply voltage	12 V DC tolerance: +/- 10 % 24 V DC tolerance: +/- 10 %
---------------------------	--

Maximum supply current	16 mA: receiving mode 40 mA: maximum in sending mode
------------------------	---

mounting mode	Fixed
---------------	-------

mounting support	Symmetrical DIN rail
------------------	----------------------

Height	88 mm
--------	-------

Width	72 mm
-------	-------

Depth	30 mm
-------	-------

net weight	0.1 kg
------------	--------

Mechanical robustness	Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2) : 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2) : 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2) : 27 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2) : 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2) : 2 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2) : 1 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Fc) : 2 Hz...13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
-----------------------	--

Maximum cable distance between devices	10 Devices <180 m at 12 V DC 10 Devices <750 m at 24 V DC 20 Devices <160 m at 12 V DC 20 Devices <450 m at 24 V DC 25 Devices <125 m at 12 V DC 25 Devices <375 m at 24 V DC 5 Devices <1000 m at 24 V DC 5 Devices <320 m at 12 V DC
--	---

Auxiliary connection terminal	Earthing terminal: screw-type connector cable 2.5...50 mm <sup>2</sup> <0.2 m Earthing terminal: screw-type connector tinned copper braid 6...100 mm <sup>2</sup>
-------------------------------	--

Tightening torque

Earthing terminal: 2.2 N.m

## Environment

<b>Electromagnetic compatibility</b>	<p>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 60255-22-1</p> <p>1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 2.5 kV DM, conforming to ANSI C37.90.1</p> <p>100 kHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 61000-4-12</p> <p>Conducted disturbance emission: (emission tests), conforming to IEC 60255-25</p> <p>Conducted disturbance emission: (emission tests), A, conforming to EN 55022</p> <p>Disturbing field emission: (emission tests), conforming to IEC 60255-25</p> <p>Disturbing field emission: (emission tests), A, conforming to EN 55022</p> <p>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 4 kV contact, conforming to ANSI C37.90.3</p> <p>Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 6 kV contact, conforming to IEC 60255-22-2</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), 4kV, 2.5 kHz, conforming to ANSI C37.90.1</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), A and B, 4kV, 2.5 kHz/2 kV, 5 kHz, conforming to IEC 60255-22-4</p> <p>Fast transient bursts: (immunity tests-conducted disturbances), IV, 4kV, 2.5 kHz, conforming to IEC 61000-4-4</p> <p>Immunity to conducted RF disturbances: (immunity tests-conducted disturbances), III, 10 V, conforming to IEC 60255-22-6</p> <p>Immunity to magnetic fields at network frequency: (immunity tests-radiated disturbances), IV, 30 A/m (continuous)-300 A/m (1-3 s), conforming to IEC 61000-4-8</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), 10 V/m, 80 MHz... 1 GHz, conforming to IEC 60255-22-3</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz... 1 GHz, conforming to ANSI C37.90.2</p> <p>Immunity to radiated fields: (immunity tests-radiated disturbances), III, 10 V/m, 80 MHz...2 GHz, conforming to IEC 61000-4-3</p> <p>Surges: (immunity tests-conducted disturbances), III, 2 kV CM, 1 kV DM, conforming to IEC 61000-4-5</p> <p>Voltage interruptions: (immunity tests-conducted disturbances), 100 % during 100 ms, conforming to IEC 60255-11</p>
--------------------------------------	---

<b>Climatic withstand</b>	<p>Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 °C, 0.5 ppm H2S, 1 ppm SO2 conforming to IEC 60068-2-60</p> <p>Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm SO2, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60</p> <p>Continuous exposure to damp heat (in operation) : Cab: 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78</p> <p>Continuous exposure to damp heat (in storage) : Cab: 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78</p> <p>Continuous exposure to damp heat (in storage) : Db: 6 days, 95 % RH, 55 °C conforming to IEC 60068-2-30</p> <p>Exposure to cold (in operation) : Ad: - 25 °C conforming to IEC 60068-2-1</p> <p>Exposure to cold (in storage) : Ab: - 25 °C conforming to IEC 60068-2-1</p> <p>Exposure to dry heat (in operation) : Bd: 70 °C conforming to IEC 60068-2-2</p> <p>Exposure to dry heat (in storage) : Bb: 70 °C conforming to IEC 60068-2-2</p> <p>Salt mist (in operation) : Kb/2: 6 days conforming to IEC 60068-2-52</p> <p>Temperature variation with specified variation rate (in storage) : Nb: - 25 °C to 70 °C, 5 °C/min conforming to IEC 60068-2-14</p>
---------------------------	--

<b>ambient air temperature for operation</b>	-25...70 °C
--	-------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.000 cm
<b>Package 1 Width</b>	12.100 cm
<b>Package 1 Length</b>	18.300 cm
<b>Package 1 Weight</b>	140.000 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	8

<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	1.460 kg
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	64
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	25.560 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)