

# CAL5-11



## CAL5-11 Auxiliary Contact Block



### General Information

Extended Product Type	CAL5-11
Product ID	1SBN010020R1011
EAN	3471522121073
Catalog Description	CAL5-11 Auxiliary Contact Block
Long Description	CAL5-11 Auxiliary Contact Block

### Ordering

EAN	3471522121073
Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

### Dimensions

Product Net Width	12 mm
Product Net Height	74 mm
Product Net Depth / Length	62 mm
Product Net Weight	0.050 kg

### Container Information

Package Level 1 Units	2 piece
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	3471522121073
Package Level 2 Units	240 piece
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	2880 piece

### Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

### Additional Information

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
----------------------	---

Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	A9 ... A75 10 million A95 ... A110 3 million A145 ... AF750 2 million
Minimum Switching Capacity	A9 ... A75 17 / 5 volt per milliamp A95 ... AF750 24 / 50 volt per milliamp
Mounting on Contactors	A 9...A 110
Mounting Position	Side
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Order Multiple	2 piece
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Product Main Type	Accessories for Block Contactors
Product Name	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x I <sub>e</sub> AC-15
Rated Frequency (f)	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1	10 x I <sub>e</sub> AC-15
Rated Operational Current AC-15 (I <sub>o</sub> )	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13 (I <sub>o</sub> )	(125 V) 0.55 / 69 A (24 V) 6 / 144 A (250 V) 0.3 / 75 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 24 V
Remarks	100
Technical Information	AUXILIARY SWITCH
Terminal Type	Screw Terminals

## Certificates and Declarations (Document Number)

CB Certificate	CB_SE_30113
CCC Certificate	CCC_2013010304604041 CCC_2004010305133985
CSA Certificate	CSA_1033838
Data Sheet, Technical Information	1SBC100122C0202_Ch04
Declaration of Conformity - CE	1SBD250809U1000
EAC Certificate	EAC_RU C-FR ME77 B01048
Environmental Information	1SBD250138E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407744P0001
RINA Certificate	RINA_ELE128713XG001
RoHS Information	1SBD350058R1000
UL Certificate	UL_071301E48139

## Classifications

---

E-nummer	3228820
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
Object Classification Code	K
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

