

Product datasheet

Specifications



circuit breaker Compact NSX250F - TMD - 250 A - 3 poles 3d

LV431630

! Discontinued on: 2 May 2023

! Discontinued

Main

| | |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range | ComPact |
| Product name | ComPact NSX |
| Range of product | ComPact NSX100...250 |
| Device short name | NSX250F |
| Product or component type | Circuit breaker |
| device application | Distribution |
| Number of poles | 3P |
| Protected poles description | 3t |
| [In] rated current | 250 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 85 kA at 240 V AC 50/60 Hz conforming to UL 508 22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 480 V AC 50/60 Hz conforming to UL 508 30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 15 kA at 600 V AC 50/60 Hz conforming to UL 508 |
| Performance level | F 36 kA 415 V AC |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit protection functions | LI |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|----------------------------------------|-------------------|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

| | |
|------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ics] rated service short-circuit breaking capacity | 35 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 8 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles |
| Electrical durability | 5000 cycles at 690 V In 10000 cycles at 690 V In/2 10000 cycles at 440 V In 20000 cycles at 440 V In/2 |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 mm |
| Protection type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip unit rating | 250 A at 40 °C |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
| [Ir] long-time protection pick-up adjustment range | 0.7...1 x In |
| Long-time protection delay adjustment type tr | Fixed |
| [tr] long-time protection delay adjustment range | 120...400 s at 1.5 x In 15 s at 6 x Ir |
| Short-time protection pick-up adjustment type Isd | Adjustable |
| [Isd] Short-time protection pick-up adjustment range | 5...10 x In |
| Short-time protection delay adjustment type tsd | Fixed |
| Earth-leakage protection | Without |
| Number of slots for electrical auxiliaries | 5 slot(s) |
| Width (W) | 105 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Net weight | 2.4 kg |

Environment

| | |
|----------------------------------------------|------------------------------|
| Standards | EN/IEC 60947 |
| Product certifications | CCC Marine EAC |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

| | |
|--------------------------|----------|
| Relative humidity | 0...95 % |
|--------------------------|----------|

| | |
|---------------------------|--------------------------------------------------------------|
| Operating altitude | 0...2000 m without derating 2000 m...5000 m with derating |
|---------------------------|--------------------------------------------------------------|

Packing Units

| | |
|-------------------------------|-----|
| Unit Type of Package 1 | PCE |
|-------------------------------|-----|

| | |
|-------------------------------------|---|
| Number of Units in Package 1 | 1 |
|-------------------------------------|---|

| | |
|-------------------------|---------|
| Package 1 Height | 13.9 cm |
|-------------------------|---------|

| | |
|------------------------|---------|
| Package 1 Width | 11.4 cm |
|------------------------|---------|

| | |
|-------------------------|---------|
| Package 1 Length | 19.5 cm |
|-------------------------|---------|

| | |
|-------------------------|----------|
| Package 1 Weight | 2.006 kg |
|-------------------------|----------|

| | |
|-------------------------------|-----|
| Unit Type of Package 2 | S04 |
|-------------------------------|-----|

| | |
|-------------------------------------|----|
| Number of Units in Package 2 | 12 |
|-------------------------------------|----|

| | |
|-------------------------|-------|
| Package 2 Height | 30 cm |
|-------------------------|-------|

| | |
|------------------------|-------|
| Package 2 Width | 40 cm |
|------------------------|-------|

| | |
|-------------------------|-------|
| Package 2 Length | 60 cm |
|-------------------------|-------|

| | |
|-------------------------|-----------|
| Package 2 Weight | 24.694 kg |
|-------------------------|-----------|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)